



## AC3 CAMERA

**Safeguard your intersections with the AC3 camera that keeps traffic flowing.** Enable early detection and dilemma zone management with the AC3 Camera for reduced congestion and safer intersections. Built-in stabilization sensors automatically adjust the frame, minimizing the impact of swaying and vibrations providing clear, steady images for accurate detection. Factory default configuration supports advanced detection, with Stop-bar configuration (SC3) available upon request.

### **Streamline your intersection with the convenient mounting kit.**

The AC3 comes with the mounting feature that allows for easy and accurate installation, saving time during the installation process.



\*Can also be ordered as a stop bar camera (SC3)

## SPECIFICATIONS

### Camera

**DIMENSIONS**

15.9" x 6.4" x 5.6" (40.4 x 16.25 x 14.2 cm)

**WEIGHT**

5.5 lbs (2.5 kg)

**MATERIAL**

Aluminum

**ENVIRONMENTAL**

NEMA TS2; -29°F to 165°F (-34°C to 74°C)

0 to 95% non-condensing

5-30Hz Vibration

10G Shock

**POWER**

Power over Ethernet (PoE)

**CONSUMPTION**

5.3W Nominal

9.7W Max

**CONNECTIVITY**

Single CAT5e Cable

**IMAGE FORMAT**

MJPEG Color

**REGULATORY**

FCC Class A

### Mounting Kit

**WEIGHT**

1.2 lbs (0.57 kg)

**WIND TUNNEL TESTED**

>150 mph

## ADDITIONAL HARDWARE

### Pole Assembly

**DIMENSIONS**

5' extension (1.52 m)

**WEIGHT**

4.8 lbs (0.57 kg)

**MATERIAL**

1.5" (3.81 cm) schedule 40 aluminum pipe - 6063-T52

### Junction Box

**CONNECTIVITY**

M12 (to Camera)

M12 (to Processor)

**DIMENSIONS**

7.8" x 2.1" x 1.4" (19.8 x 5.3 x 3.5 cm)

**WEIGHT**

0.55 lbs (.25 kg)

**MATERIAL**

Anodized Aluminum 6063 Housing

**ENVIRONMENTAL**

NEMA TS2; -29°F to 165°F (-34°C to 74°C)

**RATED**

IP67